



CommPass

Client & Restaurant Paging



A perfect entry-level guest or client paging system.

Whether you run a hospitality pub or resort, pharmacy or retail outlet multi-stack pagers can improve communications with customers and streamline business congestion. Designed to help your guests feel more connected while visiting the bar or enjoying shopping while they wait.

Designed and manufactured by JTECH (HME), the pioneer in wireless paging technology with 25 years of experience.

Pager Features

- Extremely strong
- Voice capable alert
- Advertising insert options
- User replaceable batteries
- UHF Technology
- Flexible integration

Transmitter Features

- Built with high-quality materials for maximum durability and industry leading performance.
- Easy-to-read LED backlit digital display.
- Out-of-Range and Search ensures guest contact and minimizes pager loss.
- Up to 1 mile of line-of-site coverage with unique ID to prevent signal interference.

Industries



HOSPITALITY



PHARMACY



RETAIL



PUBS/RSL/
SPORTING CLUBS



RESORT
HOTELS



MEDICAL/
PATHOLOGY



CINEMAS



MUSEUMS



CARNIVALS/
FUN PARKS



COURTS/
LEGAL

POS | CCTV | DIGITAL SIGNAGE | PAGING

**sales@vectron.com.au
1300 832 876**

**Vectron Systems (Vic) Pty Ltd.
U5, 63-71 Boundary Rd,
North Melbourne, Victoria 3051
Australia**

COMPASS PAGER TECHNICAL SPECIFICATIONS

Guest Pager Dimensions	Width	5 cm
	Depth	13.9 cm
	Height	2 cm
	Weight	0.09 kg
Rechargeable Battery	Nickel Metal Hydride (NiMH)	
	Indicator light while charging or when needs replacement	
	2-3 year pager battery life (dependent on use)	
Display	Flash, beep, vibrate, voice	
	Store and play 3 voice alerts	
	Digital number display - 3 character / 7 segment LED display	
	Blue LED charging light	

COMPASS CHARGING TOWER TECHNICAL SPECIFICATIONS

30 Stack Charging Rack Dimensions	Width	18 cm
	Depth	18 cm
	Height	34 cm
	Weight	1.8 kg
Smart Charging	Space-saving tower charger	
	Charges all pagers in 4 hours	
	Extends battery life without overcharging	

NEO TRANSMITTER TECHNICAL SPECIFICATIONS

Transmitter Dimensions	Width	10.16 cm
	Depth	19.5 cm
	Height	5 cm
	Weight	0.45 kg
Display	7.6 x 5 cm	
	4 line text display	
	LED back lit digital screen	
	Water-resistant polyurethane	
Electrical	Frequency range: 450 - 468 MHZ	
	FCC Identifier: WDC	IC Identifier: 7752A
	Channel Spacing: 12.5KHz	
	Speed / Baud Rate: 512/1200 bps	
Power	DC 12V, 3.5A, SMPS	
	RF Output: 1 Watts	
	Format: POCSAG Extended Range Technology	
Long Range Technology	UHF Frequency	
	Unique System ID eliminates interference	
	Up to 3 km of site coverage	